<u>Claims</u>

SUB () >

A lubricant composition comprising

(1) a polyalkylene glycol having the formula

RO - /CH2CH(CH3)O), - CH3

where R is an alkyl group with 1 to 15 carbon atoms and n = 1 to 35; and (2) an ester.

- 2. A lubricant composition as claimed in claim 1 wherein R is an alkyl group with 1 to 4 carbon atoms.
- 3. A lubricant composition as claimed in either of claims 1 and 2 wherein n = 8 to 30.
 - 4. A lubricant composition as claimed in any of claims 1 to 3 wherein the ester is chosen from a polyot ester, an aliphatic diacid ester, an aromatic diacid ester or a trimellitate.
- 5. A lubricant composition as claimed in claim 4 wherein the ester is either a polyol ester or an aromatic diacid ester.
- 6. A lubricant composition as claimed in any of claims 1 to 5 wherein the polyalkylene glycol is present in the range of 90-10 weight percent and the ester is present in the range of 10-90 weight percent.
- 7. A lubricant composition as claimed in claim 6 wherein the polyalkylene glycol is present in the range of 70-30 weight percent and the ester is present in the range of 30-70 weight percent.
 - 8. A lubricant composition as claimed in any of claims 1 to 7 wherein an antifoaming agent in the range 2 to 100ppm is additionally present.
 - 9. A lubricant composition as claimed in claim 8 wherein the antifoaming agent

10. A lubricant composition, for use in an air compressor, comprising

(1) a polyalkylene glycol having the formula

RO - (CH/2CH(CH3)0) - CH2

where R is an alkyl group with 1 to 15 carbon atoms and n = 1 to 35; and

(2) an ester.

Erof

STORY OF THE STORY

that